Aluphoenix Srl I Via Monte Santo 33/A
31039 Riese Pio X (TV) – Italy I P.I – C.F. IT03559100247
Tel +39 0423/199.21.08 I Fax +39 0423/199.21.09
info@aluphoenix.com I www.aluphoenix.com

Organization with an integrated management system for the quality certified according to the standard ISO9001:2015 and IATF16949:2016, and for the environment according to the standard ISO14001:2015

TECHNICAL AND SAFETY DATA SHEET

Stand. Body / Standard	UNI EN 1676:2020
Alloy Group	AlSi9Cu
Numerical designation	AB 46400
Chemical designation	AlSi19Cu1Mg

The present sheet has an information purpose and refers to typical processes.

Aluphoenix Srl will not bear any responsibility for any decision in specific processes assumed basing on it.

CHEMICAL COMPOSITION

Elements	Si	Fe	Cu	Mn	Mg	Zn	Ni	Cr	Pb	Sn	Ti	Be	Ca
Max	9.7	0.7	1.3	0.55	0.65	0.8	0.20		0.10	0.10	0.18		
Min	8.3		008	0.15	0.30								

Elements	Na	P	Sb	Sr	Co	V	Zr			Other each	Other tot.
Max										0.05	0.25
Min											

MECHANIC FEATURES ON SEPARATELY CASTED SAMPLES

Process	Treatment State	R Tensile Strenght (Mpa)	S Yeld Strenght (Mpa)	A Elongation (%)	HB Hardness in Brinnel (HBW) Ball of 10 mm and 500 Kg
Sand casting	F	135	95	1	60
Shell casting	F	170	100	1	78

PHYSICAL FEATURES (Indicative values according to the EN AB standard)

Specific weight	2.80 Kg/dm^3	**Thermal expansion from 20 to 200°C**	22 x 10^{-6}/°C
Interval of solidification and casting	540 – 570 °C	**Thermal expansion from 20 to 300°C**	23.1 x 10^{-6}/°C
Electrical conductivity	17 – 23 Ms/m	**Proper sand-casting interval**	690 – 720 °C
Thermal conductivity at 20°C	130– 160 W(m K)	**Proper shell-casting interval**	690 – 720 °C
Thermal expansion from 20 to 100°C	20.2 x 10^{-6}/°C	**Proper die-casting interval**	-

TECHNOLOGICAL FEATURES – QUALITATIVE INFORMATION

Castability	Good	**Corrosion resistance**	Sufficient
Weldability	-	**Hot Ulltimate tensile strenght**	Good
Polishing	Average	**Hot mechanical strenght**	Average
Machining workability	Sufficient	**Pressure tightness**	Average
Workability after heat treatment	Sufficient	**Indication for decorative anodiz.**	-

COMPARISON WITH EQUAL / SIMILAR INTERNATIONAL STANDARDS

	Italy	Germany	France	UK	USA	ISO	Japan
	UNI	**DIN 1725/5-86**	**NFA57-105**	**BS 1490-88**	**ASTM B179-18**	**3522-84**	**JIS H2211-92**
Equal to							
Similar to				LM 26	328.1 – 333.1		

HEAT TREATMENTS - Legend

F = Condition of the casting as it comes from the molds without any further thermal or mechanical treatment	T5 = Temper and then artificial ageing at 175°C for about 8 h	T 6 2 = Artificial ageing at 150-160°C for 8 h
O = Anneal at 350-390°C for 4-8 h (high-temperature stabilization or recrystallization treatment)	T4 = Artificial ageing at 150-160°C for about 8 h	T6 3 = Artificial ageing at 165-175°C for 16 h
Temper in hot water 510-530 °C after preheating of min 12 h for sand casted pieces. Of 8 h min for shell casted ones		

Aluphoenix Srl I Via Monte Santo 33/A
31039 Riese Pio X (TV) – Italy I P.I – C.F. IT03559100247
Tel +39 0423/199.21.08 I Fax +39 0423/199.21.09
info@aluphoenix.com I www.aluphoenix.com

Organization with an integrated management system for the quality certified according to the standard ISO9001:2015 and IATF16949:2016, and for the environment according to the standard ISO14001:2015

TECHNICAL AND SAFETY DATA SHEET

Stand. Body / Standard	UNI EN 1676:2020
Alloy Group	AlSi9Cu
Numerical designation	AB 46400
Chemical designation	AlSi19Cu1Mg

The present sheet has an information purpose and refers to typical processes.

Aluphoenix Srl will not bear any responsibility for any decision in specific processes assumed basing on it.

SAFETY PRESCRIPTIONS

IDENTIFICATION OF THE SUBSTANCE AND THE PRODUCER

The product is presented in solid state, and is intended for recasting according to different technologies and processes.

It has the shape of bars stacked and braced with plastic straps and possibly wrapped in shrinkable nylon.

The plastic material of the packaging is to be used for recovery, disposal, as waste in accordance with the current regulations on waste.

The melting of the product generates slag for recovery, disposal, as metal waste in accordance with existing waste legislation and metal foundry BAT.

Manufacturer reference for REACH information: quality1@aluphoenix.com

REACH data source: https://echa. europa. eu/it/

COMPOSITION / INFORMATION ON INGREDIENTS

The Product of Aluphoenix do not overstep concentrations of substances considered by the Regulation (UE) 2020/878 – Annex II.
According to the REACH Directive, the AlSi9Cu1Mg includes the following substances:

CAS: 7429-90-5 EC/List n°: 231-072-3	Aluminium Pyr. Sol. 1, H250; Water-react. 2. H261	85.67-88.86%
CAS: 7440-21-3 EC/List n°: 231-130-8	Silicon Flam, Sol. 2, H228	8.3-9.7%
CAS: 7440-50-8 EC/List n°: 231-159-6	Copper Flam, Sol. 1, H228; Aq. Acute 1, H400; Acute Tox. 4, H302; Eye Irrit. 2, H319; Aquatic Chronic 1, H410	0.8-1.3%
CAS: 7439-95-4 EC/List n°: 231-104-6	Magnesium Pyr. Sol. 1, H250; Water-react. 1. H260	0.3-0.65%
CAS: 7439-96-5 EC/List n°: 231-105-1	Manganese Flam. Sol. 1, H228; Aquatic Chronic 3, H412	0.15-0.55%

Labelling according to the UE Reg 1272/2008

HEALTH RISKS

1. No Harmful gas release when solid
2. No fire or explosion risk when solid. Protect from moisture
3. In the solid state it does not generate delayed symptoms.
4. There are no occupational exposure limits

STABILITY AND REACTIVITY

In the solid state, the product is stable and non-reactive to temperature and pressure. It is not soluble in water. It reacts with alkalis (lyes) and strong acidsa and hydrogen mission (H2).

PERSISTENCE AND DEGRADABILITY

Persistence: Not applicable. The product is inorganic
Biological degradability: Not degradable
Bioaccumulation capacity: Low
Long term ecotoxicity: Not classified for ecotoxicity

TOXICOLOGICAL INFORMATION

Ingestion: Ingestion < 0.1%, pratically insoluble into the pulmonary fluids. The most part of the aluminium absorbed would be quickly eliminated throught the urine.
Acute effect: No acute effects
Irritating / corrosive effect on skin: No effects
Irritating / corrosive effect on eyes: No effects. Aluminium particles can irritate eyes due abrasion effect
Carcinogenic: No known effect
Mutagenicity: No known effect
Reproductive toxicity: No known effect
Endocrine system interference: No known effect

FIRST AID MEASURES

1. **Inhalation of gas / dust during the melting phase of the product**: Provide the supply of fresh air, administer oxygen in case of shortness of breath, in case of persistence or doubts take the subject to the nearest hospital
2. **In case of skin contact with hot solid metal**: Wash the burned area of the body with adbundant cold water and apply an anti burn ointment. Cover the area of the body with a sterile gauze. In case of serious burning, bring the person to the nearest hospital
3. **In case of skin contact with hot liquid metal**: Remove the part of the clothings with molten aluminium on them, or those in contact with the burned area of the body. Wash the burned area of the body with abundant cold water and bring the person to the nearest hospital
4. **In case of contact with the eyes**: Wash the eyes with adbundant cold and clean water or/and idrate the eye with the proper eye solution. In any case quickly bring the person to the nearest hospital

HAZARDS IDENTIFICATIONS

The piles of Aluphoenix show onto two sides at least, a proper labelling against explosions hazards by inserting ingots into the melting bath, when not completely dried up.

Aluphoenix Srl I Via Monte Santo 33/A
31039 Riese Pio X (TV) – Italy I P.I – C.F. IT03559100247
Tel +39 0423/199.21.08 I Fax +39 0423/199.21.09
info@aluphoenix.com I www.aluphoenix.com

Organization with an integrated management system for the quality certified according to the standard ISO9001:2015 and IATF16949:2016, and for the environment according to the standard ISO14001:2015

TECHNICAL AND SAFETY DATA SHEET

Stand. Body / Standard	UNI EN 1676:2020
Alloy Group	AlSi9Cu
Numerical designation	AB 46400
Chemical designation	AlSi19Cu1Mg

The present sheet has an information purpose and refers to typical processes.

Aluphoenix Srl will not bear any responsibiity for any decision in specific processes assumed basing on it.

PRECAUTIONS

1. Risk of cuts by handling the ingots: Use the proper PPE to protect hands and feet
2. Scalding risk by insert the ingots into a hot melting bath. Use the proper PPE to protect face and body
3. Explosions risk by inserting moist ingots into a hot melting bath. Eventual preheat the ingots and in any case use the proper PPE to protect face and body

EXTINGUISHING MEDIA

Aluminium is non-flammable, whether solid or liquid.
If in the liquid state, for its containment in case of spillage, use dry medias of class D (sand, extinguishing powder).
Do not use water, foam, CO2 or other halogen media.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

When handling liquid aluminum: To protect yourself from the risk of burns, wear fireproof gloves and clothing including gaiters for footwear and / or fireproof aprons, protective footwear and protective visors.
To protect yourself from the risk of gas / dust inhalation, if diffuse emissions are not properly conveyed, wear a respirator: Full face mask (EN 136) (EN 136), Half mask (DIN EN 140) (EN 140), Filter type : P (EN 143) / BP (EN 141).
In case of presence of dangerous fumes, use an integrated respiratory device (EN12472, EN12941).

When handling solid, hot aluminum, wear flame retardant gloves and protective footwear. In any case, avoid contact with eyes and skin.

STORAGE

The Aluphoenix ingot piles are equipped with pallet ingots that allow handling by forklift trucks and transpallet, and their storage up to 3 levels.
Be careful to overlap the stacks so that the stacks are stable; risk of fall and injury for nearby operators.

OTHER INFORMATIONS

Index 2

• Highlighted date of revision and modification at the foot of the page

• Inserted paragraph "IDENTIFICATION OF THE SUBSTANCE AND THE MANUFACTURER"

• Updated section "COMPOSITION / INFORMATION OF INGREDIENTS" with reference to "Regulation (EU) 2020/878 – Annex II"

• Updated section "HEALTH RISKS" with the forecast of "delaying symptoms" and "occupational exposure limits"

• Added paragraph "STORAGE"

• Updated section "STABILITY AND REACTIVITY" regarding "pressure"

• Updated section "PERSISTENCE AND DEGRADABILITY" with "ecotoxicity of long-term"

• Updated section "TOXICOLOGICAL INFORMATION" with "interference with the endocrine system"